

**Product Category:** 05 41 00 - Structural Framing

**Product Name:** 800S200-68

### Project Information

Name:

Address:

### Important Properties Notes:

- Calculated properties are based on AISI S100-12 with S2-10 Supplement, North American Specification for Design of Cold-Formed Steel Structural Members.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- For deflection calculations, use the effective moment of inertia.
- Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be specified. (ex. 3.625 S137 16-50 (50 ksi))

### Contractor Information

Name:

Contact:

Phone:

Fax:

### Architect Information

Name:

Contact:

Phone:

Fax:

### Distributor/Rep Information

Name:

Contact:


Phone:

Web/Email:

## Properties

### 800S200-68 Properties

Finish:	G60
Web Depth	8 in
Flange Width	2 in
Design Thickness	0.0713 in
Thickness	68 mils or 14G
Yield stress, Fy	50 ksi
Weight	3.086 lb/ft



### 800S200-68 Section Properties

#### Gross Section Properties

Cross sectional area (A)	0.907 in <sup>2</sup>
Moment of inertia (I <sub>x</sub> )	8.143 in <sup>4</sup>
Section Modulus (S <sub>x</sub> )	2.036 in <sup>3</sup>
Radius of gyration (R <sub>x</sub> )	2.996 in
Gross moment of inertia (I <sub>y</sub> )	0.435 in <sup>4</sup>
Gross Radius of gyration (R <sub>y</sub> )	0.692 in

#### Effective Section Properties

Moment of inertia for deflection (I <sub>xe</sub> )	8.027 in <sup>4</sup>
Section modulus (S <sub>xe</sub> )	1.989 in <sup>3</sup>
Allowable bending moment (M <sub>a</sub> )	59.56 In-k
Allowable bending moment from distortional buckling (M <sub>ad</sub> )	51.46 In-k
Allowable strong axis shear away from punch-out (V <sub>ag</sub> )	4220 lb
Allowable strong axis shear at punch out (Vanet)	3367 lb

#### Torsional Properties

St. Venant torsion constant (J x 1000)	1.537 in <sup>4</sup>
Warping constant (C <sub>w</sub> )	5.712 in <sup>6</sup>
Distance from shear center to neutral axis (X <sub>o</sub> )	-1.248 in
Distance from shear center to mid-plane (M)	0.796 in
Radii of gyration (R <sub>o</sub> )	3.319 in
Torsional flexural constant (Beta)	0.859
Unbraced Length (L <sub>u</sub> )	40.4 in

**Product Category:** 05 41 00 - Structural Framing  
**Product Name:** 800S200-68

## Limiting Heights Properties

### Limiting Wall Heights – Curtain Wall 1-Span

Spacing (inches)	5psf			15psf			20psf			25psf		
	L/120	L/240	L/360	L/240	L/360	L/600	L/240	L/360	L/600	L/240	L/360	L/600
12	59'-5"	47'-2"	41'-2"	36'-10"	32'-2"	27'-1"	33'-5"	29'-3"	24'-8"	31'-1"	27'-1"	22'-10"
16	54'-0"	42'-10"	37'-5"	33'-5"	29'-3"	24'-8"	30'-5"	26'-7"	22'-5"	28'-3"	24'-8"	20'-9"
24	47'-2"	37'-5"	32'-8"	29'-3"	25'-6"	21'-6"	26'-7"	23'-2"	19'-7"	24'-8"	21'-6"	18'-2"

Spacing (inches)	30psf			35psf			40psf			50psf		
	L/240	L/360	L/600	L/240	L/360	L/600	L/240	L/360	L/600	L/240	L/360	L/600
12	29'-3"	25'-6"	21'-6"	27'-9"	24'-3"	20'-5"	26'-7"	23'-2"	19'-7"	24'-8"	21'-6"	18'-2"
16	26'-7"	23'-2"	19'-7"	25'-3"	22'-0"	18'-7"	24'-1"	21'-1"	17'-9"	22'-5"	19'-7"	16'-6"
24	23'-2"	20'-3"	17'-1"	22'-0"	19'-3"	16'-3"	20'-8"	18'-5"	15'-6"	18'-6"	17'-1"	14'-5"

### Additional Specification Information

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003.

### LEED Specification Information

**Materials & Resources Credit 2:** Construction Waste Management – Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. **(1 point)**

**Materials & Resources Credit 4:** Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

**Credit 4.1 (1 point)** Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10% (based on cost) of the total value of the materials in the project.

**Credit 4.2 (1 point)** Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

**Materials & Resources Credit 5:** Regional Materials - Contact Studs Unlimited directly for information at [bjpowell@studsunlimited.com](mailto:bjpowell@studsunlimited.com). Studs Unlimited is located in Oklahoma City, Oklahoma. **(1 point)**