

Product Category: 05 41 00 - Structural Framing

**Product Name:** 400T200-43

#### **Important Properties Notes:**

- Calculated properties are based on AISI S100-12 with S2-10
   Supplement, North American Specification for Design of Cold-Formed
   Steel Structural Members.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on fullsection of the studs, away from punchouts.
- · For deflection calculations, use the effective
- · Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be

specified. (ex. 362S162-43 (50 ksi))

### **Project Information**

Name: Address:

# **Contractor Information** Name:

Contact: Phone: Fax:

#### **Architect Information**

Name: Contact: Phone: Fax:


### **Distributor/Rep Information**

Name: Contact: Phone: Email /Web:

## **Properties**

### 400T200-43 Properties

Finish:	G60
Web Depth	4" in
Flange Width	2" in
Design Thickness	0.0451 in
Thickness	43mils or 18G
Yield stress, Fy	33 ksi
Weight	1.226 lb/ft



# 400T200-43 Section Properties

### **Gross Section Properties**

0.36 in <sub>2</sub>
1.002 In <sub>4</sub>
0.482 in <sub>3</sub>
1.668 in
0.143 in <sub>4</sub>
0.637 in

### **Effective Section Properties**

Moment of inertia for deflection (lxe	e) 0.812	in4
Section modulus (Sxe)	0.311	inз
Allowable bending moment (Ma)	6.14	In-k
Allowable bending moment from	0	In-K
distortional buckling (Mad)		
Allowable strong axis shear away	1739	lb
from punch-out (Vag)		
Allowable strong axis shear at	-	lb
punch out (Vanet)		

### **Torsional Properties**

St. Venant torsion constant (J x 1000)	0.244 In4
Warping constant (Cw)	0.436 in6
Distance from shear center to neutral	2.641 in
axis (Xo)	
Distance from shear center to	-3.13 in
mid-plane (M)	
Radii of gyration (Ro)	3.188 in
Torsional flexural constant (Beta)	0.314
Unbraced Length (Lu)	41.2 in

400T200-43 Page 1





Product Category: 05 41 00 - Structural Framing

Product Name: 400T200-43

### **Additional Specification Information**

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003.

### **LEED Specification Information**

Materials & Resources Credit 2: Construction Waste Management - Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. (1 point)

Materials & Resources Credit 4: Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

Credit 4.1 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10%(based on cost) of the total value of the materials in the project.

**Credit 4.2 (1 point)** Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

Materials & Resources Credit 5: Regional Materials - Contact Studs Unlimited directly for information at bjpowell@studsunlimited.com.

Studs Unlimited is located in Oklahoma City, Oklahoma. (1 point)

400T200-43 Page 2