

Product Category: 05 41 00 - Structural Framing

Product Name: 600T125-33

Project Information

Name:

Address:

Important Properties Notes:

- Calculated properties are based on AISI S100-12 with S2-10 Supplement, North American Specification for Design of Cold-Formed Steel Structural Members.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- For deflection calculations, use the effective moment of inertia.
- Allowable moment includes cold-work of forming.
- Web depth for track sections is equal to the nominal height plus 2 times the design thickness plus the bend radius. Hems on non-structural rack sections are ignored.

Contractor Information

Name:

Contact:

Phone:

Fax:

Architect Information

Name:

Contact:

Phone:

Fax:

Distributor/Rep Information

Name:

Contact:


Phone:

Web/Email:

Properties

600T125-33 Properties

Finish:	G90
Web Depth	6" in
Flange Width	1-1/4" in
Design Thickness	0.0346 in
Thickness	33 mills or 20G
Yield stress, Fy	33 ksi
Weight	1.000 lb/ft



600T125-33 Section Properties

Gross Section Properties

Cross sectional area (A)	0.294 in ²
Moment of inertia (Ix)	1.429 in ⁴
Section Modulus (Sx)	0.465 in ³
Radius of gyration (Rx)	2.205 in
Gross moment of inertia (Iy)	0.034 in ⁴
Gross Radius of gyration (Ry)	0.339 in

Effective Section Properties

Moment of inertia for deflection (Ixe)	1.273 in ⁴
Section modulus (Sxe)	0.279 in ³
Allowable bending moment (Ma)	5.51 In-k
Allowable bending moment from distortional buckling (Mad)	- In-k
Allowable strong axis shear away from punch-out (Vag)	3.707 lb
Allowable strong axis shear at punch out (Vanet)	- lb

Torsional Properties

St. Venant torsion constant (J x 1000)	0.117 in ⁴
Warping constant (Cw)	0.238 in ⁶
Distance from shear center to neutral axis (Xo)	-0.837 in
Distance from shear center to mid-plane (M)	0.658 in
Radii of gyration (Ro)	2.382 in
Torsional flexural constant (Beta)	0.876
Unbraced Length (Lu)	24.8 in



Product Category: 05 41 00 - Structural Framing
Product Name: 600T125-33

Additional Specification Information

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003.

LEED Specification Information

Materials & Resources Credit 2: Construction Waste Management – Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. **(1 point)**

Materials & Resources Credit 4: Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

Credit 4.1 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10%(based on cost) of the total value of the materials in the project.

Credit 4.2 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

Materials & Resources Credit 5: Regional Materials - Contact Studs Unlimited directly for information at bjpowell@studsunlimited.com. Studs Unlimited is located in Oklahoma City, Oklahoma. **(1 point)**