



www.studsunlimited.com

Product Category: 05 41 00 - Structural Framing

Product Name: 1400T125-54

Important Properties Notes:

- Calculated properties are based on AISI S100-12 with S2-10 Supplement, North American Specification for Design of Cold-Formed Steel Structural Members.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-section of the studs, away from punchouts.
- For deflection calculations, use the effective
- Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be specified. (ex. 362S162-43 (50 ksi))

Project Information

Name:

Address:

Contractor Information

Name:

Contact:

Phone:

Fax:

Architect Information

Name:

Contact:

Phone:

Fax:

Distributor/Rep Information

Name:

Contact:

Phone:

Email /Web:

Properties

1400T125-54 Properties

Finish:	G90
Web Depth	14" in
Flange Width	1 1/4 in
Design Thickness	0.0566 in
Thickness	54mils or 16G
Yield stress, F_y	50 ksi
Weight	3.175 lb/ft



1400T125-54 Section Properties

Gross Section Properties

Cross sectional area (A)	0.933 in ²
Moment of inertia (Ix)	19.987 in ⁴
Section Modulus (Sx)	2.815 in ³
Radius of gyration (Rx)	4.628 in
Gross moment of inertia (Iy)	0.061 in ⁴
Gross Radius of gyration (Ry)	0.256 in

Effective Section Properties

Moment of inertia for deflection (Ixe)	18.098 in ⁴
Section modulus (Sxe)	1.009 in ³
Allowable bending moment (Ma)	30.2 in-k
Allowable bending moment from distortional buckling (Mad)	in-K
Allowable strong axis shear away from punch-out (Vag)	1160 lb
Allowable strong axis shear at punch out (Vanet)	- lb

Torsional Properties

St. Venant torsion constant (J x 1000)	0.997 in ⁴
Warping constant (Cw)	2.559 in ⁶
Distance from shear center to neutral axis (Xo)	-0.981 in
Distance from shear center to mid-plane (M)	0.89 in
Radii of gyration (Ro)	4.738 in
Torsional flexural constant (Beta)	0.957
Unbraced Length (Lu)	17.2 in



Product Category: 05 41 00 - Structural Framing

Product Name: 1400T125-54

Additional Specification Information

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003.

LEED Specification Information

Materials & Resources Credit 2: Construction Waste Management - Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. **(1 point)**

Materials & Resources Credit 4: Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

Credit 4.1 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10% (based on cost) of the total value of the materials in the project.

Credit 4.2 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

Materials & Resources Credit 5: Regional Materials - Contact Studs Unlimited directly for information at bjpowell@studsunlimited.com. Studs Unlimited is located in Oklahoma City, Oklahoma. **(1 point)**